

TC601

A Masterpiece of Innovation, Created for Industrial Mobility



Warehouse



Logistics



Retail



Manufacturing

Accessories



Bumper

- 2-meter Drop Protection
- PC/TPU Material
- 54.3g



Pistol Grip

- Mechanical Trigger Button
- PC Material
- 132.5g



Spare Battery

- 3.85V
- 4000mAh/15.40Wh
- 72g
- Rechargeable Li-Polymer Battery Pack



Power Adapter

- Input:100-240Vac
- Output: 5V/3A; 9V/2A; 12V/1.5A



USB Cable

- Type C USB 3.0



Cradle

- L: 140mm, W:126, H: 81mm ; 330g(w/o bracket) ; 330g(w/o bracket)
- IO Port: USB 2.0 Type C and Ethernet. (Priority : Type C > Ethernet)
- Charging Slots: Support Terminal*1+Battery*1 charging at the same time
- Battery voltage: 4.4V
- RIO Connector: Type C(24pins)+2 charging pins
- Certification: EU/North America/ Taiwan
- Terminal Charging Spec: 5V/3A
- Environmental
 - Operating Temperature: -20°C ~50°C
 - Storage Temperature: -30°C ~60°C
 - Charging Temperature: 0°C ~45°C
 - Humidity: 5%~90% no condense
 - ESD: +/-4KV contact discharge, +/-8KV air discharge
 - 75 m drop to concrete

Adaptor

- Input : AC 100~240V
- Output : 19V/2.37A

Date: 2020. 10.08